

CRA SERIES

RESIDENTIAL FAN FORCED ZONAL WALL HEATERS

- **FAST-RESPONSE COIL ELEMENT ASSURES QUICK HEAT AND LOW MAINTENANCE**
- **THREE PIECE CONSTRUCTION FOR EASE OF INSTALLATION**
- **EUROPEAN STYLING: SLEEK ROUNDED CORNERS**
- **DUAL PROTECTION: THERMAL CUTOUT WITH INDICATOR LIGHT AND ONE TIME THERMAL FUSE**
- **SIENNA WHITE BAKED ENAMEL FINISH**
- **500 - 1000 WATT UNITS ARE APPROVED FOR CEILING MOUNT**



APPLICATIONS

RESIDENTIAL: Suitable for use in almost any room. Use single heaters in smaller rooms such as bedrooms and bathrooms. Use multiple heaters (controlled by a single thermostat) in larger rooms such as living rooms and family rooms. Wattage levels should be determined by heat loss calculations.

COMMERCIAL APPLICATIONS: Suitable as the primary heat source in smaller rooms and as supplemental heat in almost any general use area.

MOUNTING LIMITATIONS

Do not install back box closer than 4.5 inches from floor, adjacent walls and 12 inches from ceiling. Units 1000W or less can be ceiling mounted. Do not install heater behind towel rack, behind door, in floor, in closet, or where airflow may be obstructed. To insure proper operation, maintain 5-foot minimum clearance to furniture or other objects placed directly in front of the heater.

ACCESSORIES

CATALOG NO.	DESCRIPTION
CRABB	Back Box only
CRABB6	Back multi-pack (Used with "IF" suffix models)
CRATDP	D.P. Thermostat Kit (Range: 40-85°)
CRASM	Surface mounting frame

SELECTION CHART

CATALOG NO.	VOLTS**	WATTS	BTU/HR.	AMPS	CATALOG NO.	VOLTS**	WATTS	BTU/HR.	AMPS
CRA0512-T2	120	500	1706	4.2	CRA1012-IF	120	1000	3412	8.3
CRA1012-T2	120	1000	3412	8.3	CRA1512-IF	120	1500	5118	12.5
CRA1512-T2	120	1500	5118	12.5	CRA2028-IF	208	2000	6824	9.6
CRA1024-T2	240/208	1000/750	3412/2559	4.5/3.6	CRA0724-IF	240/208	750/563	2559/1921	3.1/2.7
CRA1524-T2	240/208	1500/1125	5118/3839	6.3/5.4	CRA1024-IF	240/208	1000/750	3412/2559	4.5/3.6
CRA2024-T2	240/208	2000/1500	6824/5118	8.3/7.2	CRA1524-IF	240/208	1500/1125	5118/3839	6.3/5.4
CRA2224-T2	240/208	2250/1688	7677/5760	9.4/8.1	CRA2024-IF	240/208	2000/1500	6824/5118	8.3/7.2
					CRA2224-IF	240/208	2250/1688	7677/5760	9.4/8.1

CRA-****-T2(Complete unit):
Heater assembly, grille, back box and factory installed DP thermostat (Range: 40-85°F)

CRA-****-IF (Inner Frame):
IF models include heater assembly and grille only
Order back box Cat. No. CRABB separately.

** Single phase 60 Hz. A.C.; 240 Volt units will operate on 208 Volt with 25% reduction in output.

NOTE: For installations over 7500 feet above sea level we recommend using models under 1500 watts.

