


CRN SERIES INDUSTRIAL PERMANENT INFRARED HEATERS

- **HEAVY DUTY STRAIGHT METAL SHEATH HEATING ELEMENT**
- **UL AND CUL APPROVED**
- **1.0, 1.5, 2.0 AND 2.5 KW HEAT OUTPUTS AVAILABLE**
- **VOLTAGES INCLUDE 120, 208, 240, 277 AND 347**
- **SINGLE PHASE OPERATION ONLY**
- **HEATER CAN BE WASHED DOWN - AFTER BEING DISCONNECTED**
- **SAFETY GRILLES AVAILABLE**



APPLICATIONS

The lower watt density industrial permanently installed infrared heaters are designed to provide heavy-duty spot heating and is a good source of heat for use in areas where dependence on air movement is impractical. Loading docks, walkways, assembly areas, enclosed smoking areas, repair stations and storage areas are just a few examples of where the CRN Series infrared heaters can be used.

HEATER SELECTION CHART

CATALOG NUMBER	WATTS	VOLTS	PHASE	REFLECTOR ANGLE	ELEMENT TYPE	SHIP WT.	AVAIL.
CRN1011	1,000	120	1	90° Symm	Metal Sheath	10 lbs	S
CRN1081		208					NS
CRN1021		240					S
CRN1511	1,500	120	1	90° Symm	Metal Sheath	15 lbs	S
CRN1581		208					NS
CRN1521		240					S
CRN1571		277					NS
CRN1531		347					NS
CRN2001	2,000	208	1	90° Symm	Metal Sheath	18 lbs	S
CRN2021		240					S
CRN2071		277					NS
CRN2031		347					NS
CRN2501	2,500	208	1	90° Symm	Metal Sheath	20 lbs	S
CRN2521		240					S
CRN2571		277					NS
CRN2531		347					NS

DESCRIPTION

The CRN Series infrared heater is an excellent choice for spot heating. Often, a series of spot heat areas can be incorporated within the total area to avoid maintaining a higher ambient temperature throughout the building or room. Comfort levels will depend on the intensity of the

wattage output. The CRN Series has four wattage outputs to choose from and starting as low as 1KW.

The construction of the CRN Series heater is simple. Aluminum extruded housing keeps the heating element secure while providing a focal point where a highly polished aluminum


reflector extends over the assembly to provide a uniform heating pattern.

The heating element connects to a gasketed, moisture resistant terminal enclosure. This allows the heater to be washed down provided the heater is disconnected from the power supply.

WIRE GUARDS & HANGING KITS

CATALOG NUMBER	QUANTITY REQUIRED	DESCRIPTION	SHIP WT.	AVAIL.
CRNWG01	1	Wire guard for use with 1KW CRN heaters	3 lbs	S
CRNWG105	1	Wire guard for use with 1.5 KW CRN heaters	5 lbs	S
CRNWG200	1	Wire guard for use with 2.0 KW CRN heaters	7 lbs	S
CRNWG250	1	Wire guard for use with 2.5 KW CRN heaters	10 lbs	S
BRMHK	1	Hanging Kit. Includes chain & hooks	2 lbs	S

DIMENSIONS



MOUNTING LIMITATIONS:
Minimum Mounting Height from floor to bottom of heater is 8 feet.



470 Beauty Spot Rd. E, Bennettsville, SC 29512

Distributed By:

