



## TYPE CBD HEAVY-DUTY COMMERCIAL BASEBOARD HEATERS

- Heavy-duty construction
- 16 gauge front cover
- Built-in wireway
- Large wiring compartment

CBD Series heavy-duty baseboard, with its complete line of accessories and controls, can solve the space heating needs of virtually any type commercial structure. Individual room control allows you to heat each room separately for utmost energy savings.




**CONSTRUCTION** - This heavy-duty baseboard is designed specifically for commercial use. The front cover is made of 16 gauge cold rolled steel. A built-in wireway runs the length of each heater.

**ELEMENT** - Heating element design combines the durability of a steel tubular heater with the excellent heat transfer characteristics of aluminum fins.

**JUNCTION BOXES** - Identical prewired junction boxes at each end are large and roomy to work from the side or the front of the heater. Knockouts are provided in the backside or the bottom of each heater end.



FILE #E37116



### SELECTION CHART

CATALOG NUMBER	HEATER VOLTS	WATTS	BTU/HR	AMPS	LENGTH	WT. (lbs.)
CBD500	120	500	1706	4.2	28"	7
CBD508	208	500	1706	2.4		
CBD504	240/208	500/375	1706	2.1/1.8		
CBD507	277/240/208	500/375/282	1706	1.8/1.6/1.4		
CBD750	120	750	2560	6.3	34"	9
CBD758	208	750	2560	3.6		
CBD754	240/208	750/562	2560	3.1/2.7		
CBD757	277/240/208	750/562/422	256	2.7/2.3/2.0		
CBD1000	120	1000	3413	8.3	46"	12
CBD1008	208	1000	3413	4.8		
CBD1004	240/208	1000/750	3413	4.2/3.6		
CBD1007	277/240/208	1000/750/562	3413	3.6/3.1/2.7		
CBD1250	120	1250	4265	10.4	58"	15
CBD1258	208	1250	4265	6.0		
CBD1254	240/208	1250/938	4265	5.2/4.5		
CBD1257	277/240/208	1250/938/704	4265	4.5/3.9/3.4		
CBD1500	120	1500	5120	12.5	70"	19
CBD1508	208	1500	5120	7.2		
CBD1504	240/208	1500/1125	5120	6.3/5.4		
CBD1507	277/240/208	1500/1125/844	5120	5.4/4.7/4.1		
CBD2008	208	2000	6826	9.6	94"	26
CBD2004	240/208	2000/1500	6826	8.3/7.2		
CBD2007	277/240/208	2000/1500/1125	6826	7.2/6.3/5.4		

### ACCESSORIES

CATALOG NUMBER	DESCRIPTION	WT. (LBS.)
HBBT1	25A @ 120-277V SPST Thermostat	1
HBBT2	25A @ 120-277V DPST Thermostat	1
HBBT1TP	Same as HBBT1 except tamper proof.	1
HBBT2TP	Same as HBBT2 except tamper proof.	1
HBBAC	Air conditioner outlet section, 20A, @ 208-240V	1
HBBDR	Duplex receptacle section, 15A @ 120V	1
HBBLVRO	Low voltage Relay Section, 25A @ 120V	2
HBBLVR8	Low voltage Relay Section, 25A @ 208V	2
HBBLVR4	Low voltage Relay Section, 25A @ 240V	2
HBBCDS2	2-Pole Disconnect switch section	1
CBDCIC	Inside corner section	1
CBDCOC	Outside corner section	1
HBBWS	8" Wiring section	1
CBDBS2	2 FT. BLANK SECTION	5
CBDBS3	3 FT. BLANK SECTION	8
CBDBS4	4 FT. BLANK SECTION	10
CBDBS5	5 FT. BLANK SECTION	13
CBDBS6	6 FT. BLANK SECTION	15
CBDBS8	8 FT. BLANK SECTION	21