


HSN, HSW & RHSW

Half & Full Sheath Ring Heaters



- Narrow Ring (type HSN)
- Wide Ring (type HSW)
- Split Rivet/Wide Ring (type RHSW)
- 500 - 1,000 Watts
- 120 and 240 Volt
- Use Ring Clamp 6018 to Mount Element to Heated Surface

Dimensions



Features

Single-Heat Rings — Have two terminals for single wattage on-off switch or thermostat.

Three-Heat Rings — Have three terminals that split the heater into 2 equal circuits. Center terminal is common.

Easy Installation — Circular shape and use of Chromalox utility clamps simplifies use of ring heaters.

Nesting Rings to pack heat in a small area.

Half Sheath Units Have Reduced Thermal Gradient to Heated Surface — Provides faster heat up.



Full Sheath Only



HSW & RHSW Full & Half Sheath



Full Sheath Only



Full Sheath Only

Strip and Ring

Specifications and Ordering Information

Dimensions (In.)			Rust-Resisting Iron Sheath						Chrome Steel Sheath						Wt. (Lbs.)		
A	B	C	Watts	W/In ²	Model	120V		240V		Watts	W/In ²	Model	120V			240V	
						Stock	PCN	Stock	PCN				Stock	PCN	Stock	PCN	
HSN — Half Sheath																	
6	4-5/16	1/4	500	14	HSN-6	S	185818										0.5
6	4-5/16	1/4	800	12	HSN-6			S	185826								0.5
6	4-5/16	1/4								500	14	HSN-60	S	185834			0.5
6	4-5/16	1/4								500	14	HSN-60			S	185842	0.5
HSW — Full Sheath																	
6	3-3/4	1/4	1,000	24	HSW-61	S	185877										0.5
HSW — Half Sheath																	
5-7/8	3-9/16	7/32	500	16	HSW-5	S	185746										0.5
5-7/8	3-9/16	7/32	750	23	HSW-5			S	185738								0.5
6	3-3/4	1/4	500	12	HSW-6	S	185754										0.5
6	3-3/4	1/4	500	12	HSW-6			S	185762								0.5
6	3-3/4	1/4	700	17	HSW-6	S	185770										0.5
6	3-3/4	1/4	700	17	HSW-6			S	185789								0.5
6	3-3/4	1/4	700	17	HSW-6-3	S	185797										0.5
6	3-3/4	1/4	700	17	HSW-6-3			S	185800								0.5
6	3-3/4	1/4								500	12	HSW-60	S	185850			0.5
6	3-3/4	1/4								800	20	HSW-60			S	185869	0.5
6	3-3/4	1/4								1,000	24	HSW-60-3	S	255767			0.5
6	3-3/4	1/4								750	18	HSW-60-3			S	255759	0.5
RHSW — Half Sheath																	
6	3-3/4	1/4	350	8	RHSW-6-3	S	185893										0.6
6	3-3/4	1/4	500	12	RHSW-6	NS	185922										0.6
RHSW — Full Sheath																	
6	3-3/4	1/4	800	19	RHSW-61	S	185906										0.6
6	3-3/4	1/4	800	19	RHSW-61-3			NS	185914								0.6

Stock Status: S = stock AS = assembly stock NS = non-stock
To Order—Specify model, PCN, watts, volts and quantity.

1. "-3" in model number indicates 3 heat.

Other Note — Type HSN is not CSA Certified.