

High Temperature Inert Atmosphere Ovens

Inert atmosphere ovens for operation at up to 1250°F. Protect parts from oxidation using any non-flammable gas such as Nitrogen, Argon or Carbon Dioxide. Front-to-back horizontal air flow completely surrounds work on shelves or large parts placed directly on the optional reinforced work space bottom. Includes cooling jacket which can be equipped with optional cooling blower and automatic dampers. Installation of optional atmosphere purge solenoid, cooling blower and programming temperature controller provides completely automatic sequencing.

STANDARD FEATURES

- **UL LISTED CONTROL PANEL**
- Standard Inert Atmosphere Ovens from Grieve meet the requirements of National Fire Protection Association Standard 86, Industrial Risk Insurers, Factory Mutual and OSHA standards. For some applications, such as those involving hazardous locations, the above organizations require additional safety devices.
- **Controls**
 - Digital, microprocessor based, thermocouple actuated, indicating temperature controller
 - Motor control push buttons
 - On-off heat switch
 - LED pilot lights
- **Safety Equipment**
 - Adjustable, thermocouple actuated, manual reset excess temperature controller
 - Separate heating element control contactors
 - Recirculating blower air flow safety switch
- **Construction**
 - All interior seams welded gas-tight
 - All wall penetrations welded at inside and fitted with compression fitting at outside of oven
 - Silicone rubber atmosphere seal at outside perimeter of oven door
 - High temperature inner door gasket with stainless steel spring insert to seal heat in oven and protect atmosphere seal
 - 2-point cam action positive latching door hardware
 - Adjustable offset door hinges to guarantee tight closure of door seal
 - Exterior blower shaft seal
 - Inert atmosphere inlet with pressure regulator to maintain positive pressure within oven
 - 0-200 CFH atmosphere flow meter
 - Pressure gauge to indicate interior oven pressure
 - Inert atmosphere outlet with pressure relief
 - Air jacket on inner oven for cooling
 - Front-to-back horizontal air flow
 - 16 gauge 304 stainless steel interior
 - Aluminized steel exterior with enamel finish
 - Brushed stainless steel control panel face
 - Insulated with 2" thick 1900°F insulating block, backed up with 10 lbs/cf density industrial rockwool
 - Built-in baffles prevent radiant heat
 - Two (2) stainless steel wire shelves
 - Channel shelf supports prevent shelves tipping
 - 1 year limited warranty
- **Every oven fully assembled and individually factory tested**



**1050°F AND 1250°F
FRONT-TO-BACK
HORIZONTAL AIR FLOW
INERT ATMOSPHERE OVENS**



MODEL IA-1250

WITH OPTIONAL PROGRAMMABLE TEMPERATURE
CONTROLLER, AUTOMATIC DOOR SWITCH AND 24"
INTEGRAL OVEN LEGS



SPECIFICATIONS

NOT FOR USE WITH FLAMMABLE SOLVENTS, VAPORS OR GASES.

| Model | Work Space | | Outside Dimensions* (WxDxH) | Max Temp | Blower | | Insulation | Doors | KW | Operating Characteristics† | | | Approx Shipping Weight |
|---------|--------------------|--------------|-----------------------------|----------|--------|-----|------------|--------|----|----------------------------|-----------------|-----------|------------------------|
| | Dimensions (WxDxH) | Volume Cu Ft | | | CFM | HP | | | | Control Accuracy | Oven Uniformity | Rise Time | |
| IA-1050 | 24" x 24" x 24" | 8 | 53" x 60" x 47½" | 1050°F | 600 | 1/2 | 10" | Single | 12 | ±0.3% | ±10°F | 80 min | 2445 lbs |
| IA-1250 | 24" x 24" x 24" | 8 | 57" x 64" x 51½" | 1250°F | 1000 | 3/4 | 12" | Single | 18 | ±0.3% | ±13°F | 90 min | 2815 lbs |
| IB-1050 | 24" x 36" x 24" | 12 | 53" x 72" x 47½" | 1050°F | 1000 | 3/4 | 10" | Single | 12 | ±0.3% | ±10°F | 100 min | 2740 lbs |
| IB-1250 | 24" x 36" x 24" | 12 | 57" x 76" x 51½" | 1250°F | 1200 | 1 | 12" | Single | 18 | ±0.3% | ±13°F | 111 min | 3265 lbs |
| IC-1050 | 36" x 36" x 36" | 27 | 65" x 70" x 59½" | 1050°F | 1000 | 3/4 | 10" | Single | 18 | ±0.3% | ±10°F | 115 min | 3475 lbs |
| IC-1250 | 36" x 36" x 36" | 27 | 69" x 74" x 63½" | 1250°F | 1200 | 1 | 12" | Single | 24 | ±0.3% | ±13°F | 129 min | 4240 lbs |
| ID-1050 | 36" x 48" x 36" | 36 | 65" x 82" x 59½" | 1050°F | 1200 | 1 | 10" | Single | 18 | ±0.3% | ±10°F | 140 min | 4410 lbs |
| ID-1250 | 36" x 48" x 36" | 36 | 69" x 86" x 63½" | 1250°F | 1400 | 1½ | 12" | Single | 24 | ±0.3% | ±13°F | 170 min | 4845 lbs |

*All Models—Control panel overhang 9" right side. Blower motor overhang 18" rear.

†Accuracy as percent of controller span. Uniformity at 100°F below maximum temperature. Rise Time in minutes to 100°F below maximum temperature. Tests run with empty oven and minimum exhaust. Performance will vary with load and application. See Bulletin TC-920 for additional details.

STANDARD EQUIPMENT

- 208 volts, 3-phase, 60 Hz
- 230 volts, 3-phase, 60 Hz
- 460 volts, 3-phase, 60 Hz
- Other electrical characteristics available


Each features completely wired, side access UL listed control panel enclosing terminals for incoming power, temperature controllers, push buttons and pilot lights. Motor starter and heating element contactors electrically interlocked to shut off heaters if power to blower is interrupted and to permit operation of blower without heat for cooling. Incoloy sheathed tubular heating elements. The 1250°F models have a heat chamber high limit controller. Two (2) reinforced 100 lbs uniformly distributed load capacity, stainless steel wire shelves. Models IA and IB will hold seven (7) shelves on 3" centers; models IC and ID five (5) shelves on 6" centers.

Trilite Green enamel painted aluminized steel exterior. Insulated with 2" of 1900°F insulating block backed up with 1250°F industrial rockwool.

Inert atmosphere is introduced at blower shaft (1/2" NPT) and positive oven pressure maintained by inlet pressure regulator. Atmosphere flow indicated on 0-200 CFH flow meter. Oven pressure indicated on 0-5 inch water column pressure gauge. Continuously welded inner oven construction with compression fittings at wall penetrations maintains atmosphere integrity. Atmosphere outlet equipped with pressure relief which can be manually opened to increase inert gas flow for initial purge of air from oven. Adjustable positive latching door hardware and offset hinges assure positive door seal. The inner high temperature gasket seals directly against the door plug; outer atmosphere gasket seals against the front face of the oven.

ADDITIONAL EQUIPMENT AVAILABLE*

- **Additional Shelves**, 100 lbs distributed load per shelf, 400 lbs maximum oven load, specify oven model when ordering.
- **Programmable Temperature Controller**, microprocessor based, digital indicating, thermocouple actuated, in lieu of standard controller **PTC3**
- **Recording Thermometer**, thermocouple actuated, 24-hour, 10" diameter circular chart used in conjunction with standard controller (side mounted) **RT**
- **Programmable Recording Temperature Controller**, microprocessor based, thermocouple actuated, digital display, 24-hour, 10" diameter circular chart, in lieu of standard controller (side mounted) **PRTC3**
- **Digital Timing Temperature Controller**, microprocessor based, digital indicating, incorporates 99 hour 59 minute timer, starts timing when temperature reaches set point and shuts down oven at end of set time **DTS3**
- **Shut Down Timer**, with continuous "hold" feature; 1, 5, 10 or 30 hour range **SDT**
- **Batch Timer**, for uniformly timing batch operations. Continuous alarm with door interlock; alarms at end of preset time period until door is opened or timer reset; 1, 5, 10 or 30 hour range **BT**
- **Automatic Door Switch**, turns off blower and heat when door is opened. Restores blower and heat when door is closed **ADS**
- **Integral Oven Legs**, with 1/8" steel plate shelf. 24" high on IA & IB series, 16" high on IC & ID series **ISTND**
- **Removable Oven Stand**, with 1/8" steel plate shelf. 24" high on IA & IB series, 16" high on IC & ID series **RSTND**
- **500 lbs Capacity Stainless Steel Subway Grating**, oven work space bottom. Reduces work space height by 1". Specify oven model when ordering **SUB**
- **Modulating Dampers** to regulate cool down rate, replaces 2-position dampers included with cooling blower. Includes heating/cooling programmable temperature controller in lieu of optional programmable temperature controller required with cooling blower **MD**



| Oven Model | Capacity | HP | Outlet Dia | Approx Cooling to 250°F from | |
|------------|----------|-----|------------|------------------------------|---------|
| | | | | 1000°F | 1250°F |
| IA | 325 CFM | 1/3 | 6" | 95 min | 110 min |
| IB | 650 CFM | 1/2 | 6" | 60 min | 70 min |
| IC | 975 CFM | 1 | 8" | 80 min | 100 min |
| ID | 975 CFM | 1 | 8" | 110 min | 130 min |

*See Bulletin TC-920 for modifications and other optional equipment.

Represented By: Ross & Pethtel
Phone: 225-273-2202 Website