


ARMTO-2

Light Weight Oil Applications



- 2" NPT Steel Screw Plug
- Steel Sheath Elements
- 23 - 26 W/In²
- 1.5 - 6 kW
- Integral Thermostat (DPST)
- 120, 208, 240 and 480 Volt, Single Phase
- General Purpose Terminal Enclosure

E1 — Dimensions (Inches)



Specifications and Ordering Information

							T3 — Temperature (200 - 550°F)			T2 — Temperature (60 - 250°F)			T1 — Temperature (0 - 100°F)		
kW	Volts	Phase	W/In ²	No. Elem.	DIM B (In.)	Wt. (Lbs.)	Model	Stock	PCN	Model	Stock	PCN	Model	Stock	PCN
E1 General Purpose¹															
1.5	120	1	24	2	11-3/4	6	ARMTO-2155T3	S	270570	ARMTO-2155T2	S	271097	ARMTO-2155T1	S	274159
1.5	208	1	24	2	11-3/4	6	ARMTO-2155T3	AS	322843	ARMTO-2155T2	AS	322851	ARMTO-2155T1	AS	322860
1.5	240	1	24	2	11-3/4	6	ARMTO-2155T3	S	270588	ARMTO-2155T2	S	271100	ARMTO-2155T1	S	274167
1.5	480	1	24	2	11-3/4	6	ARMTO-2155T3	AS	274909	ARMTO-2155T2	S	274933	ARMTO-2155T1	S	274175
2	120	1	24	2	17-3/4	7	ARMTO-2205T3	AS	270609	ARMTO-2205T2	S	274941	ARMTO-2205T1	AS	284023
2	208	1	24	2	17-3/4	7	ARMTO-2205T3	AS	322907	ARMTO-2205T2	AS	322915	ARMTO-2205T1	AS	322923
2	240	1	24	2	17-3/4	7	ARMTO-2205T3	AS	270617	ARMTO-2205T2	S	271118	ARMTO-2205T1	AS	283830
2	480	1	24	2	17-3/4	7	ARMTO-2205T3	AS	283370	ARMTO-2205T2	S	284066	ARMTO-2205T1	AS	274950
2.5	120	1	26	2	19-5/8	8	ARMTO-2255T3	AS	285510	ARMTO-2255T2	AS	274968	ARMTO-2255T1	AS	285501
2.5	208	1	26	2	19-5/8	8	ARMTO-2255T3	AS	322966	ARMTO-2255T2	AS	322974	ARMTO-2255T1	AS	322982
2.5	240	1	26	2	19-5/8	8	ARMTO-2255T3	AS	270641	ARMTO-2255T2	AS	284103	ARMTO-2255T1	AS	284090
2.5	480	1	26	2	19-5/8	8	ARMTO-2255T3	AS	274917	ARMTO-2255T2	AS	274140	ARMTO-2255T1	AS	284138
3	120	1	23	2	24-7/8	8	ARMTO-2305T3	AS	285560	ARMTO-2305T2	AS	274976	ARMTO-2305T1	AS	285552
3	208	1	23	2	24-7/8	8	ARMTO-2305T3	AS	323029	ARMTO-2305T2	AS	323037	ARMTO-2305T1	AS	323045
3	240	1	23	2	24-7/8	8	ARMTO-2305T3	S	270676	ARMTO-2305T2	S	271134	ARMTO-2305T1	AS	283821
3	480	1	23	2	24-7/8	8	ARMTO-2305T3	AS	274925	ARMTO-2305T2	S	274183	ARMTO-2305T1	AS	284200
4	120	1	23	2	32-3/4	9	ARMTO-2405T3	AS	285616	ARMTO-2405T2	AS	285608	ARMTO-2405T1	AS	274984
4	208	1	23	2	32-3/4	9	ARMTO-2405T3	AS	323088	ARMTO-2405T2	AS	323096	ARMTO-2405T1	AS	323109
4	240	1	23	2	32-3/4	9	ARMTO-2405T3	AS	270705	ARMTO-2405T2	AS	271142	ARMTO-2405T1	AS	284234
4	480	1	23	2	32-3/4	9	ARMTO-2405T3	AS	284285	ARMTO-2405T2	AS	284277	ARMTO-2405T1	AS	284269
5	120	1	23	2	40-1/4	9	ARMTO-2505T3	AS	285667	ARMTO-2505T2	AS	285659	ARMTO-2505T1	AS	274992
5	208	1	23	2	40-1/4	9	ARMTO-2505T3	AS	323141	ARMTO-2505T2	AS	323150	ARMTO-2505T1	AS	323168
5	240	1	23	2	40-1/4	9	ARMTO-2505T3	AS	270730	ARMTO-2505T2	S	271150	ARMTO-2505T1	AS	284322
5	480	1	23	2	40-1/4	9	ARMTO-2505T3	AS	284373	ARMTO-2505T2	AS	284365	ARMTO-2505T1	AS	284357
6	208	1	23	2	47-3/4	10	ARMTO-2605T3	AS	323205	ARMTO-2605T2	AS	323213	ARMTO-2605T1	AS	323221
6	240	1	23	2	47-3/4	10	ARMTO-2605T3	AS	270756	ARMTO-2605T2	AS	284429	ARMTO-2605T1	AS	284410
6	480	1	23	2	47-3/4	10	ARMTO-2605T3	AS	284189	ARMTO-2605T2	AS	284470	ARMTO-2605T1	AS	284461

Stock Status: S = stock AS = assembly stock NS = non-stock
To Order—Specify model, volts, phase, kW, PCN and quantity.

1. Heaters are UL Listed with T1 or T2 Temperature and CSA Certified with T1, T2 or T3 Temperature.