


EMTS-3


Mildly Corrosive Solution Applications

- 2" NPT Stainless Steel Passivated Screw Plug
- Stainless Steel Passivated Sheath Elements
- Medium Watt Density (23 W/In²)
- 3 - 9 kW
- Without Thermostat
- 240 and 480 Volt, Three Phase
- General Purpose or Moisture Resistant/Explosion Resistant Terminal Enclosure

E1 — Dimensions (Inches)



E2 — Dimensions (Inches)



Screw Plug

Specifications and Ordering Information

						E1 General Purpose ¹				E2 Moisture Resistant/Explosion Resistant ²			
kW	Volts	Phase	W/In ²	No. Elem.	DIM B (In.)	Model	Stock	PCN	Wt. (Lbs.)	Model	Stock	PCN	Wt. (Lbs.)
3	240	3	23	3	17-3/4	EMTS-3030	S	091686	6	EMTS-3030E2	AS	033398	9
3	480	3	23	3	17-3/4	EMTS-3030	S	091694	6	EMTS-3030E2	AS	033400	9
4.5	240	3	23	3	24-7/8	EMTS-3045	S	091707	7	EMTS-3045E2	AS	033419	10
4.5	480	3	23	3	24-7/8	EMTS-3045	S	091715	7	EMTS-3045E2	AS	033427	10
6	240	3	23	3	32-7/16	EMTS-3060	S	091723	9	EMTS-3060E2	AS	033435	12
6	480	3	23	3	32-7/16	EMTS-3060	S	091731	9	EMTS-3060E2	AS	033443	12
7.5	240	3	23	3	40-3/8	EMTS-3075	S	091740	10	EMTS-3075E2	AS	033451	13
7.5	480	3	23	3	40-3/8	EMTS-3075	S	091758	10	EMTS-3075E2	AS	033460	13
9	240	3	23	3	47-7/8	EMTS-3090	S	091766	12	EMTS-3090E2	AS	033478	15
9	480	3	23	3	47-7/8	EMTS-3090	S	091774	12	EMTS-3090E2	AS	033486	15

Stock Status: S = stock AS = assembly stock NS = non-stock
To Order—Specify model, volts, phase, kW, PCN and quantity.

1. Heaters with General Purpose Enclosures are UL Listed and CSA Certified.
2. Heaters with Moisture Resistant/Explosion Resistant Enclosures are CSA NRTL/C Certified.