


MTO-LT

Pipe Insert Applications

- 2" NPT Steel Screw Plug
- INCOLOY® Sheath Element
- 12 W/In²
- 4 - 13 kW
- 240 and 480 Volt, Single Phase
- Moisture Resistant/Explosion Resistant Terminal Enclosure
- Without Controls

Dimensions (Inches)



Features

- Low Watt Density to permit operation in dead air space of pipes
- Insertion into 2" Dia. pipes
- Install or Remove heater without draining tank
- Avoids coking or charring of heat sensitive materials as pipe surface functions as low watt density heat transfer surface

Applications

- Asphalt
- Heavy Weight Fuel Oil
- Heavy Weight Lubricating Oil
- Tar
- Molasses
- Other High Viscosity Materials

Specifications and Ordering Information

kW	Volts	Phase	W/In ²	Dimensions (In.)		Model	Stock	PCN	Wt. (Lbs.)
				A	B				
4	240	1	12	127	120	MTO-241LT	S	253155	12
4	480	1	12	127	120	MTO-241LT	S	186036	12
5	240	1	12	163	156	MTO-251LT	S	186044	16
5	480	1	12	163	156	MTO-251LT	NS	253180	16
7.5	240	1	12	211	204	MTO-275LT	NS	253198	22
7.5	480	1	12	211	204	MTO-275LT	NS	253200	22
11.5	480	1	12	319	312	MTO-212LT	NS	253219	36
13	480	1	12	367	360	MTO-213LT	NS	253227	42

Stock Status: S = stock AS = assembly stock NS = non-stock
To Order—Specify model, volts, phase, kW, PCN and quantity.

1. Higher kW available. Contact your Local Chromalox Sales office.