

Over-the-Side Immersion Heaters

Optional Accessories

- Thermal Fuses
- Thermowells
- Thermowell Guards

Fuse



Thermowell



Fuse — Specifications and Ordering Information

For Heater Models	Lead Length (In.)	Temp. Rating (°F)	Single Use Fuse		Reset Fuse		Stock
			Model	PCN	Model	PCN	
GS, GT, 3GS, 3GT	18	219	F	360330	RF	360436	S
GS, GT, 3GS, 3GT	18	260	FM ¹	360348	RFM	360444	S
GS, GT, 3GS, 3GT	18	330	FH	360356	RFH	360452	S
GTF, GTFN	18	219	FT	360364	RFT	360460	S
GTF6, GTF9	18	260	FTM ¹	360372	RFTM	360479	S
QM, QM3	18	330	FTH	360380	RFTH	360487	S
GSL, GTL	86	219	FL	360399	RFL	360495	S
GSL3, GTL3	86	260	FLM ¹	360401	RFLM	360508	S
GSV3, GTV3	86	330	FLH	360410	RFLH	360516	S
GTFL, GTFNL, GTFL3	86	260	FLTM ¹	360428	RFLTM	360524	S
Resettable Fuse Circuitry ²	—	All	—	—	RFM-EC	360321	S

Stock Status: **S** = stock AS = assembly stock NS = non-stock
To Order—Specify model, PCN and quantity.

1. Standard fuse shipped from factory on stock items that feature thermal fuse.
2. Reset fuse is bi-metal switch only and requires connection to Resettable Fuse System Circuitry, Model RFM-EC, PCN 360321, which must be ordered separately. RFM-EC includes manual reset, audible alarm and relay (rated to 240V, 5A)

Other Note — Solution temperatures must always be a minimum of 50°F below fuse temperature rating.

Thermowell — Specifications and Ordering Information

Well Material	ID/OD (In.)	12" Length		24" Length		36" Length		Stock
		Model	PCN	Model	PCN	Model	PCN	
316 SS	0.43 / 1/2	GSTW-12	360575	GSTW-24	360612	GSTW-36	360655	S
Titanium	0.43 / 1/2	GTTW-12	360583	GTTW-24	360620	GTTW-36	360663	S
Fluoropolymer ¹	0.44 / 1/2	GTFTW-12	360591	GTFTW-24	360639	GTFTW-36	360671	S
Quartz ¹	0.50 / 5/8	GQTW-12	360604	GQTW-24	360647	GQTW-36	360680	S
Thermowell Guards — made of Polypropylene²								
Fluoropolymer Well Guard	—	GTFTW-12G	360698	GTFTW-24G	360719	GTFTW-36G	360735	S
Quartz Well Guard	—	GQTW-12G	360700	GQTW-24G	360727	GQTW-36G	360743	S

Stock Status: **S** = stock AS = assembly stock NS = non-stock
To Order—Specify model, volts, phase, kW and PCN.

1. Guards recommended. (See Thermowell Guards listed above.)
2. Other materials available. Contact your Local Chromalox Sales office.

Other Notes —

- A. Bracket dimensions: 1" wide x 4" long. 3/8" mounting hole centered 3/16" from end.
- B. Other lengths, diameters and sheath materials available. Contact your Local Chromalox Sales office.