


# Immersion

## TTUH


### Food Equipment Water Applications

- Bottom Mounted
- Brass Flange
- Copper Sheath Elements
- 1 - 12 kW
- 120, 208, 240 and 480 Volt,  
1 & 3 Phase
- Without Integral Thermal  
Cutout
- High Watt Densities (see Table)


#### Dimensions (Inches)



#### Dimensions (Inches)



#### Dimensions (Inches)



Flanged

#### Applications

- Coffee Urns
- Steam Tables
- Kettles
- Humidifiers

#### Specifications and Ordering Information

kW	Volts	W/In <sup>2</sup>	Dimensions (In.)				Model	Stock	PCN	Wt. (Lbs.)	No. Elements
			A	B	C	D					
<b>1 Phase w/o Cutout — 2" Min. Liquid Depth</b>											
1	120	42	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-10A	S	272321	3	1
1.5	120	57	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-15A	S	272330	3	1
1.5	208	57	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-15A	S	272348	3	1
1.5	240	57	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-15A	S	272356	3	1
2	120	57	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-20A	S	272364	3	1
2	208	57	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-20A	S	272372	3	1
2	240	57	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-20A	S	272380	3	1
2.5	120	58	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-25A	S	272399	3	1
2.5	208	58	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-25A	S	272401	3	1
2.5	240	58	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-25A	S	272410	3	1
3	120	55	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-30A	S	272428	3	1
3	208	55	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-30A	S	272436	3	1
3	240	55	6-3/4	4-9/16	4-1/4	2-5/16	TTUH-30A	S	272444	3	1
4	120	53	9-1/2	4-9/16	4	1-3/8	TTUH-40A	S	272452	3	1
4	208	53	9-1/2	4-9/16	4	1-3/8	TTUH-40A	S	272460	3	1
4	240	53	9-1/2	4-9/16	4	1-3/8	TTUH-40A	S	272479	3	1
5	208	39	12-3/4	4-9/16	4	1-11/16	TTUH-50	S	192583	5	1
5	240	39	12-3/4	4-9/16	4	1-11/16	TTUH-50	S	192591	5	1
6	208	42	14-1/2	4-9/16	4	1-11/16	TTUH-60	S	192604	6	2
6	240	42	14-1/2	4-9/16	4	1-11/16	TTUH-60	S	192612	6	2
7	208	49	14-1/2	4-9/16	4	1-11/16	TTUH-70	NS	192620	6	2
7	240	49	14-1/2	4-9/16	4	1-11/16	TTUH-70	S	192639	6	2
<b>3 Phase w/o Cutout — 3" Min. Liquid Depth</b>											
3	208	55	8-3/4	4-5/8	3-1/8	1-15/16	TTUH-303	S	255943	4	3
3	240	55	8-3/4	4-5/8	3-1/8	1-15/16	TTUH-303	S	255951	4	3
4	208	74	8-3/4	4-5/8	3-1/8	1-15/16	TTUH-403	S	255960	4	3
4	240	74	8-3/4	4-5/8	3-1/8	1-15/16	TTUH-403	S	255978	4	3
4	480	74	8-3/4	4-5/8	3-1/8	1-15/16	TTUH-403	NS	258511	4	3
5	208	73	11	4-5/8	3-1/8	1-15/16	TTUH-503	S	255986	5	3
5	240	73	11	4-5/8	3-1/8	1-15/16	TTUH-503	S	255994	5	3
6	208	67	11-1/16	5	4-1/16	2-3/8	TTUH-603	S	256006	5	3
6	240	67	11-1/16	5	4-1/16	2-3/8	TTUH-603	S	256014	5	3
6	480	67	11-1/16	5	4-1/16	2-3/8	TTUH-603	S	258520	5	3
7	208	78	11-1/16	5	4-1/16	2-3/8	TTUH-703	S	256022	5	3
7	240	78	11-1/16	5	4-1/16	2-3/8	TTUH-703	S	256030	5	3
8	208	69	11-1/8	5	4-1/16	2-3/8	TTUH-803	S	258423	5	3
8	240	69	11-1/8	5	4-1/16	2-3/8	TTUH-803	S	258431	5	3
12	240	98	17-3/4	5	4-1/16	2-3/8	TTUH-1203	NS	186052	6	3

**Stock Status:** S = stock AS = assembly stock NS = non-stock  
**To Order**—Specify model, PCN, kW, volts, phase and quantity.